

Product-/datasheet

10 mm Bamboo Extreme Industrial parquet™

Technical service

Manufacturer	Holse & Wibroe A/S
Vat no.	CVR-nr. 28281439
Address	Agenavej 16, 2670 Greve
Phone	+45 88 18 28 00
E-mail	Info@holseogwibroe.dk
Web-address	www.holseogwibroe.dk

Specifikations

Item number	140300, 145700	EN 13501-1: C _{fl} -s1
Color	Natural or Carbonized	
Thickness	10 mm	
Width	300 mm	
Length	200 mm	
Density	Approx. 1.050 kg/ cbm	
Hardness	9,5 kg/mm ² (Brinell)	
Package content	1,92 m ²	
Weight/ box	20 Kg.	
Construction	Solid	
Shrink/ Swell	0,14% per 1% change in moisture content	
Equilibrium MC	8% at 20 dgr. & 50% Relative air humidity	
Thermal conductivity	0,17 W / (m·K)	
If not mentioned, standards are accordingly to EN 14342		

Surface

Unfinished.

Installation & Maintenance

Installation	Must be fully glued to the subfloor. Accordingly, to the relevant installation instruction, on the time of the installation. See guidance at www.holseogwibroe.dk
Maintenance & Care	See guidance at www.holseogwibroe.dk

June 2023